


# GP Batteries

## DATA SHEET

<b>Description</b>	: Lithium Battery
<b>Chemical System</b>	: Lithium Manganese Dioxide
<b>Nominal Voltage</b>	: 3.0 Volts
<b>Nominal Capacity</b>	: 800mAh @ 10mA to 1.8V at 23°C
<b>Dimensions</b>	: Ø15.3 mm x 26.5 mm
<b>Terminals</b>	: Flat
<b>Jacket</b>	: PVC Resin Label
<b>Shelf Life</b>	: Up to 10 years
<b>Average Weight</b>	: App. 10g
<b>Max. Constant Current</b>	: 1000mA
<b>Max. Pulse Current</b>	: 2500mA
<b>Application</b>	: Smoke Detector, Sensors, Home Security Products
<b>Operating Temperature</b>	: -40°C to +60°C
<b>UL Standard</b>	: UL1642 (File no. MH46184) UL2054 (File no. MH25972)
<b>IEC Standard</b>	: IEC60086-4
<b>UN Standard</b>	: UN38.3

Model No.: **GPCR2**

Ultra+




Unit : mm


### Cross References:

JIS	GP	Panasonic	Energizer	Duracell
CR15H270	CR2	CR-2	EL1CR2	DLCR2

### Discharge Characteristics 900mA, 3 seconds on / 27 seconds off



### Continuous Discharge at 23°C



The information (subject to change without prior notice) contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult your nearest GP Sales and Marketing Office or Distributors.

[www.gpbatteries.com](http://www.gpbatteries.com)

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.  
Copyright@ GPI International Ltd. - All rights reserved